



**Consent For Operation
(CFO-Air,Water)**

**Consent No. AW-332838
Valid upto: 30/06/2027**

**Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax:080-25586321
email id: ho@kspcb.gov.in**

Industry Colour: RED Industry Scale: LARGE

Application Type: CFO-
Renewal

(This document contains 5 pages including annexure & excluding additional

Combined Consent Order No. AW-332838 **PCB ID:** 35496 **Date:** 19/08/2022

Combined consent for discharge of effluents under the Water (Prevention and Control of Pollution) Act , 1974 and emission under the Air (Prevention and Control of Pollution) Act , 1981

- Ref: 1. Application filed by the applicant/organization on 15/07/2022
2. Inspection of the Industry/organization/by RO, on 12/07/2022
3. Proceedings of the ECM dated , held on

Consent is hereby granted to the Occupier under Section 25(4) of the Water (Prevention & Control of Pollution) Act, 1974 (herein referred to as the Water Act) & Section 21 of Air (Prevention & Control of Pollution) Act, 1981, (herein referred to as the Air Act) and the Rules and Orders made there under and authorized the Occupier to operate /carryout industry/activity & to make discharge of the effluents & emissions confirming to the stipulated standards from the premises mentioned below and subject to the terms and conditions as detailed in the Schedule Annexed to this order.

Location:

Name of the Industry: Harsha Sugars Limited
Address: Sy No. 411/1, 411/2, 413/1, 412, 411/3, 417/2, Soundatti Village, Soundatti Tq, Belagavi-Dist
Industrial Area: Not In I.A., Savadatti,
Taluk: Savadatti , District: Belgaum

CONDITIONS:

a) Discharge of effluents under the Water Act:

Sr	Water Code	WC(KLD)	WWG(KLD)	Remark
1	Cooling Water	422.000	222.000	The spray pond overflow water shall be treated in the ETP along with washing and other effluents and used for on land irrigation within the premises.
2	D.M Water Plant	84.000	9.000	DM Plant reject shall be used for dust suppression in bagasse and ash storage area.
3	Domestic Purpose	25.000	22.000	The sewage shall be disposed to septic tank and soak pits designed as per IS 2470 -1985 (Part-1 & 2) till installation of STP as per the affidavit. There shall not be any overflow from the septic tank and soak pits
4	Manufacturing Processes	3079.000	0.000	The process water shall be treated and reused completely
5	Others	22.000	22.000	The washing effluent shall be treated in ETP and used for on land irrigation within the premises
6	Others	22.000	22.000	

b) Discharge of Air emissions under the Air Act from the following stacks etc.

Sl. No.	Description of chimney/outlet	Limits specified refer schedule
The details of Sources, control equipments and its specification, type of fuel, constituents to be controlled in emissions etc. are detailed in Annexure-II.		

The consent for operation is granted considering the following activities/Products;

Sr	Product Name	Applied Qty	Unit
1	power generation	14.0000	Mega Watt
2	sugar cane crushing	4500.0000	Tonnes Crushed Per Day (TCD)

This consent is valid for the period from 01/07/2022 to 30/06/2027

To,
Harsha Sugars Limited
Plot No. 151, 2nd Stage,
Opp: Hanuman Temple,
Hanuman Nagar, Belagavi.



**Consent For Operation
(CFO-Air,Water)**

Consent No. AW-332838
Valid upto: 30/06/2027

Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax:080-25586321
email id: ho@kspcb.gov.in

Industry Colour: RED Industry Scale: LARGE

Application Type: CFO-
Renewal

(This document contains 5 pages including annexure & excluding additional

COPY TO:

The Environmental Officer, KSPCB, Regional Office Belgaum for information and necessary action.

2. Master Register.
3. Case file.

Consent Fee paid : Rs. 4000000

SCHEDULE

TERMS AND CONDITIONS

A. TREATMENT AND DISPOSAL OF EFFLUENTS UNDER THE WATER ACT.

1. The discharge from the premises of the occupier shall pass through the terminal manhole/manholes where from the Board shall be free to collect samples in accordance with the provisions of the Act/Rules made there under.

2(a). The sewage/domestic effluent shall be treated in septic tank and with soak pit. No overflow from the soak pit is allowed. The septic tank and soak pit shall be as per IS 2470 Part-I & Part-II.

2(b). The treated sewage effluent discharged shall conform to the standards specified in Annexure-I.

3(a). The trade effluent generated in the industry shall be treated in the ETP and treated effluent shall conform to the standards stipulated by the Board in Annexure-I

3(b). The trade effluent shall be handed over to CETP and maintain logbook of effluent generated & sent every day.

4. The applicant shall install flow measuring/recording devices to record the discharge quantity and maintain the record.

5. The applicant shall not change or alter either the quality or the quantity or the place of discharge or temperature or the point of discharge without the previous consent/ permission of the Board.

6. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises. Storm water shall not be allowed to mix with the effluents on the upstream of the terminal manhole where the flow measuring devices are installed.

7. The daily quantity of domestic effluent and trade effluent from the industry shall not exceed the limits as indicated in this consent order:

8. The applicant shall discharge the effluents only to the place mentioned in the Consent order and discharge of treated/untreated outside the premises is not permitted.

B. EMISSIONS:

1. The discharge of emissions from the premises of the applicant shall pass through the air pollution control equipment and discharged through stacks/chimneys mentioned in **Annexure-II** where from the Board shall be free to collect the samples at any time in accordance with the provisions of the Act and Rules made there under. The tolerance limits of the constituents forming the emissions in each of the stacks shall not exceed the limits laid down in Annexure-II.

2. The applicant shall provide port holes for sampling of emission, access platforms for carrying out stack sampling, electrical points and all other necessary arrangements including ladder as indicated in Annexure-II.

3. The applicant shall upgrade/modify/replace the control equipment with prior permission of the Board.

C. MONITORING & REPORTING:

1. The applicant shall get the samples of effluents & emissions collected and get them analyzed once a month/either by in house monitoring laboratory or through EP approved laboratories for the parameters as Indicated in Annexure I & II.

2. The applicant shall maintain log books to reflect the working condition of pollution control systems and also self monitoring results and keep it open for inspection.



**Consent For Operation
(CFO-Air,Water)**

**Consent No. AW-332838
Valid upto: 30/06/2027**

**Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax: 080-25586321
email id: ho@kspcb.gov.in**

Industry Colour: RED Industry Scale: LARGE

Application Type: CFO-
Renewal

(This document contains 5 pages including annexure & excluding additional

D. SOLID WASTE (OTHER THAN HAZARDOUS WASTE) DISPOSAL:

1. The applicant shall segregate solid waste from Hazardous Waste, Municipal Solid Waste and store it properly till treatment/disposal without causing pollution to the surrounding Environment.
2. The solid waste generated shall be handled & disposed by scientific method without causing eye sore to the general public and to the surrounding environment.

E. NOISE POLLUTION CONTROL:

The applicant shall ensure that the ambient noise levels within its premises during construction and during operational period shall not exceed w.r.t Area/Zone as per Noise Pollution (Regulation and Control) Rules, 2000 as mentioned below:-

- a) In Industrial Area 75 dB(A) Leq during day time and 70 dB(A) Leq during night time.
- b) In Commercial Area 65 dB(A) Leq during day time and 55 dB(A) Leq during night time.
- c) In Residential Area 55 dB(A) Leq during day time and 45 dB(A) Leq during night time.
- d) In Silence Zone 50 dB(A) Leq during day time and 40 dB(A) Leq during night time.

Note: - * Day time shall mean 6 am to 10 pm and Night time shall mean 10 pm to 6 am.

* dB(A) Leq denotes the time weighted average of the level of sound in decibels on scale A which is relatable to human hearing.

* A "decibel" is a unit in which noise is measured.

* "A", in dB(A) Leq, denotes the frequency weighting in the measurement of noise and corresponds to frequency response characteristics of the human ear.

* Leq: It is an energy mean of the noise level over a specified period.

F. HAZARDOUS AND OTHER WASTES (MANAGEMENT & TRANSBOUNDARY MOVEMENT) Rules 2016:

The applicant shall comply with the provisions of the Hazardous and other Wastes (Management & Transboundary Movement) Rules 2016.

G. GENERAL CONDITIONS:

1. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises.
2. The applicant shall promptly comply with all orders and instructions issued by the Board from time to time or any other officers of the Board duly authorized in this behalf.
3. The applicant shall set-up Environmental Cell comprising of qualified and competent personnel for complying with the conditions specified.
4. The Board reserves the right to review, impose additional conditions, revoke, change or alter terms and conditions of this consent.
5. The applicant shall forthwith keep the Board informed of any accidental discharge of emissions/effluents into the atmosphere in excess of the standards laid down by the Board. The applicant shall also take corrective steps to mitigate the impact.
6. The applicant shall provide alternate power supply sufficient to operate all Pollution control equipments.
7. The entire premises shall always be kept clean. The effluent holding area, inspection chambers, outlets, flow measuring points should be made easily approachable.
8. The applicant shall display the consent granted in a prominent place for perusal of the inspecting officers of the Board.
9. The applicant his heirs, legal representatives or assignee shall have no claims whatsoever to the continuation or renewal of this consent after expiry of the validity of consent.



**Consent For Operation
(CFO-Air,Water)**

**Consent No. AW-332838
Valid upto: 30/06/2027**

**Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax:080-25586321
email id: ho@kspcb.gov.in**

Industry Colour: RED Industry Scale: LARGE

Application Type: CFO-
Renewal

(This document contains 5 pages including annexure & excluding additional

10. The applicant shall make an application for consent for subsequent period at least 45 days before expiry of this consent.
11. The applicant shall develop and maintain adequate green belt all around the periphery.
12. The applicant shall provide rain water harvesting system and shall provide proper storm water management system.
13. This consent is issued without prejudice to any Court Cases pending in any Hon'ble Court
14. The applicant shall furnish the Environmental statement for every financial year ending with 31st March in Form-V as per Environment (Protection) Rules, 1986. The statement shall be furnished before the end of September.
15. The applicant shall display flow diagram of the pollution control system near the pollution control system/s.

NOTE:

The Conditions A(3b) mentioned in the schedule are not applicable.

Additional Conditions:

1. The occupier shall comply with all the Additional Conditions and Standards stipulated in Annexures-A & B attached with this consent order.
2. This consent order contains 13 pages including Additional Conditions and Annexures.
3. The products with quantities, water consumption, waste water generation, mode of disposal with standards, air pollution sources with control measures mentioned in Additional Conditions attached with this order shall be considered and to be complied by the industry.

Chi m.N o.	Chimne y attached to	Capacity/ KVA Rating	Minimum chimney height to be provided above ground level (in Mts)	Constituents to be controlled in the emission	Tolerance limits mg/NM3	Fuel	Air pollution Control equipment to be installed, in addition to chimney height as per col.(4)	Date of which air pollution control equipments shall be provided to achieve the stipulated tolerance limits and chimney heights conforming to stipulated heights.
1	D.G. Sets	750 KVA DG	30	PM,SO ₂ ,NO _x ,CO, NMHC	-,-,-,-,-	DIE	AEC	At all times
2	Boiler	Boiler - 140 TPH	70	PM,SO ₂ ,NO _x ,CO, NMHC	115,-,-,-,-	BAG	ESP,PRT	At all times

Note:

AEC : Accoustic Enclosures

ESP,PRT : E.S.P

Note:

1. The Noise levels within the premises shall not exceed 75 dB (A) leq during day time and 70 dB(A) leq during night time respectively.
2. The DG set shall be provided with acoustic measures as per SI.No.94 in Schedule-I of Environment (Protection) Rules.
3. There shall be no smell or odour nuisance from the industry.



**Consent For Operation
(CFO-Air,Water)**

Consent No. AW-332838
Valid upto: 30/06/2027

Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax: 080-25586321
email id: ho@kspcb.gov.in

Industry Colour: RED Industry Scale: LARGE

Application Type: CfO-
Renewal

(This document contains 5 pages including annexure & excluding additional

LOCATION OF SAMPLING PORTHOLES, PLATFORMS, ELECTRICAL OUTLET.

1. Location of Portholes and approach platform:

Portholes shall be provided for all chimneys, stacks and other sources of emission. These shall serve as the sampling points. The sampling point should be located at a distance equal to atleast eight times the stack or duct diameters downstream and two diameters upstream from source of low disturbance such as a Bend, Expansion, Construction Valve, Fitting or Visible Flame for rectangular stacks, the equivalent diameter can be calculated from the following equation.

$$\text{Equivalent Diameter} = \frac{2 (\text{Length} \times \text{Width})}{(\text{Length} + \text{Width})}$$

2. The diameter of the sampling port should not be less than 100 mm dia". Arrangements should be made so that the porthole is closed firmly during the non sampling period
3. An easily accessible platform to accommodate 3 to 4 persons to conveniently monitor the stack emission from the portholes shall be provided. Arrangements for an Electric Outlet Point of 230 V 15 A with suitable switch control and 3 Pin Point shall be provided at the Porthole location.
4. The ladder shall be provided with adequate safety features so as to approach the monitoring location with ease.

For and on behalf of the
Karnataka State Pollution Control Board